

Step 8 Attach an earring hook to the ring on the R₃ hoop.



Step 9 Create a second earring.



Design by Helena Chmelíková

PRECIOSA Rocailles

331 19 001; 10/0







Preciosa Ornela introduces seed beads from the PRECIOSA Traditional Czech Beads $^{\text{TM}}$ brand.

Preciosa-Ornela.com



Circles

Choose seed beads in the trending colors for Autumn and Winter 2024/2025 and use this tutorial to make a pair of playful earrings. The circles interconnect and create an attractive, moving unit.

Materials and tools:

PRECIOSA Solgel Rocailles (R)

331 19 001; 10/0; 02681 light yellow; ca 200x (**R1**)

331 19 001; 10/0; 02692 pink; ca 220x (**R2**)

331 19 001; 10/0; 02634 turquoise; ca 240x (**R3**)

- memory wire (MW) with a 50 mm, 55 mm and 60 mm diameter; 4 mm rings; earring hooks; rubber stoppers for earring hooks



- large snipping pliers for sturdy wire; a pair of flat-nosed pliers; a measuring tape; needle-nosed pliers or pliers with a rounded point



Difficulty:

Technique: stringing, linking

Procedure:

Step 1 Snip a 2 to 3 cm piece of MW from each diameter.



Twist a horizontally placed eye on one end of the MW. Grasp the end of the wire between rounded points at the tip. Turn the pliers and the wire will twist around the point. It will probably be necessary to change your grip on the pliers/move them several times. The MW is tough and resilient. Twist gently backwards at the place where the end of the MW approaches the MW hoop, so that the eye is centrally located. You can squeeze the eye from the side and close it with the flat-nosed pliers. You can also modify it into a horizontal position.





Step 3
String the rocailles onto the hoop.
String 15.7 cm (up to 100x R1) onto
the 50 mm MW, 17.2 cm (up to 110x R2)
onto the 55 mm MW and 18.8 cm (up to 120x
R3) onto the 60 mm MW. Fill almost the
entire hoop. String a rubber stopper onto
the memory wire. Use the tape measure
to measure the entire length of the R along
the outer circumference of the stringing.
Remove the stopper and alter the length
(add or remove beads) if necessary.





Step 4
Remove the stopper.
Hold the last **R** with one hand.
Use you second hand to shorten
the protruding MW to 8 – 10 mm (8 mm –
an almost pointed, rounded point and
10 mm – a round point with a flat surface)
with the snipping pliers. Grip the edge
of the protruding MW and twist an eye.
You can also adjust it using the flat-nosed
pliers. Both eyes should be in the same
opposite position. You can also adjust
the entire hoop with delicate movements.





Step 5 Connect the eyes on the **R1** hoop using a ring and two flat-nosed pliers.





Step 6
Open a new ring.
Thread it through the eye on the R2 hoop,
the ring on the R1 hoop and the second eye
on the R2 hoop.





Step 7 Open a new ring. Thread it though the eye on the R3 hoop, the ring on the R2 hoop and the second eye on the R3 hoop.